

Recovery unit VRR12L-OS-R32



Refrigerant: category III	R-12,R-134a,R-401C,R-500,1234yf
Refrigerant: category IV	R-22,R-401A,R-401B,R-402B,R-407C,R-407D,R-408A,R-409A,R-411A,R-411B,R-412A,R-502,R509
Refrigerant: category V	R-402A,R-404A,R-407B,R-410A,R-507,R-32
Power supply	230/50 V/Hz
Motor	3/4 HP
Motor speed	1450 rpm
Maximal current draw	4A
Compressor	Oil-less, Air-cooled, Piston-style
Automatic safety Shut-off	38.5bar/3850kPa(558psi)

Recovery unit VRR12L-OS-R32

Recovery rate : category III - vapor / liquid / push/pull	0,20 / 1,60 / 4,60 kg/min
Recovery rate : category IV - vapor / liquid / push/pull	0,25 / 1,80 / 5,60 kg/min
Recovery rate : category V - vapor / liquid / push/pull	0,25 / 2,20 / 6,30 kg/min
Operating temperature	0 ÷ 40 °C
Dimensions	450 x 250 x 355mm
Weight	14.2 kg
Set	Shoulder strap, dry filter, 15 cm hose, ¼" x ¼", O.F.P. hose

Pictures of some products may vary. Every effort has been made to ensure that the information contained in this catalog is correct. Due to constant technological development, we reserve the right to make changes without notice.

Recovery unit VRR12L-OS-R32

Refrigerant recovery unit with oil separator is used for the recovery of refrigerant HFC and HCFC.

The main features:

- rapid recovery of refrigerant
- with oil separator
- little handy recovery unit
- equipped with a high and low pressure gauge
- manual reset
- one knob for easy operation

O.F.P. hose it is used for connection with cylinders overfill sensor.



Recovery unit VRR12L-OS-R32

